

**Straight Linear Fusing Press HP-600LF,HP-600LFS****Specifications**

This is a continuous type machine therefore production is greatly increased.

The automatic Belt Warping Prevention Device keeps both the upper and lower belts in the same position. Using the feed back system, damage is prevented. (Patent Pending)

Using the electronic thermostat and the SSR, the temperature difference's range is kept at  $\pm 3^{\circ}\text{C}$ . The SSR's electronic parts have no contact points making for durability.

Various stackers can be used with this machine.

This machine has a front conveyor belt which greatly increases production levels.

The Rotary Strip Off Device can be attached as optional equipment.

By pushing the heater control switch the temperature of the upper and lower or front and rear heater can be easily controlled. This means various materials can be used safely.

The pressure roller is covered with a layer of silicon rubber. The upper and lower pressure rollers are completely separated when the pressure is set at 0.

The heating plate is covered with special hard alumite, making it durable. The exchange of belts is very easy.

The Belt Stopping Device stops the belt automatically if the belt warps therefore protecting the belt.

The entrance of the feed in point can be adjusted easily according to the thickness of the material and interlining being used.

An anti puckering roller is installed in this machine. This roller's position can be adjusted.

Wing tables can be attached to the work table. When these tables are not in use, they can be folded down. (Option)

The pressure is easily adjusted.

Depending on which of the optional tables is used, various shapes can be easily pressed.

## Straight Linear Fusing Press HP-600LF,HP-600LFS



本体

Now Printing

Scraper Device

Now Printing

Strip-Off Device

Description	Straight Linear Fusing Press
Model	HP-600LF,LFS
Voltage	3P200V / 3P380V
Rated Output	Heater : 8.4kw Motor : 250W/275W
Fusing Width	600mm
Belt Speed (MAX)	10.2m/minutes
Presser (MAX)	62N/cm2 (6.04kg/cm2)
Temperature (MAX)	195℃
Heating Time	6~28 second
Size	1,200×1,190×3,100mm
Weight	380kg

## ■ 対象製品イラスト



[TOP](#)[SPECIFICATIONS](#)[OPTION](#)[YOU MAY ALSO BE  
INTERESTED IN:](#)

## Straight Linear Fusing Press HP-600LF,HP-600LFS

### Standard

Strip-Off device (HP-600LFS)

### Option

Cooling Fun / Slide Rail Stacker (HS-3030RS)

### Consumption

Teflon Belt

TOP

SPECIFICATIONS

OPTION

YOU MAY ALSO BE  
INTERESTED IN:

## Straight Linear Fusing Press HP-600LF,HP-600LFS



▶ **HP-600LF**



▶ **HP-600LFS**



▶ **HP-900LF with  
Scraper  
Device**



▶ **HP-900LFS  
with Strip-Off  
Device**