

Flat Type Fusing Press HP-125FA**Specification**

In case of emergencies, just push the emergency button to raise the upper plate. The upper plate is coated with an anti-static Teflon sheet for soil-free operation. Any adhesive or other impurity which sticks to the plate can be removed with ease so that materials are always kept clean. Uses a special heater which exhibits excellent thermal efficiency and assures a long service life. Aluminum is used for the upper plate, and the electronic thermostat and SSR controls the temperature difference range to within $\pm 4^{\circ}\text{C}$. A 300W blow motor makes a powerful vacuum, and provides extra sucking power.

Flat Type Fusing Press HP-125FA



Description

Flat Type fusing Press

Model

HP-125FA

Voltage

3P200V

Power

Heater : 4,500W
Motor : 400W
Vaccum : 300W

Max. Voltage

17.5A

Dimension

1,200mm×500mm

Temperature (MAX)

200℃

Presser (MAX)

380g/cm²

Size (Body)

1,200(W)×1,170(D)×1,550(H)mm

Weight

380kg

■ 対象製品イラスト



[TOP](#)[SPECIFICATIONS](#)[OPTION](#)[YOU MAY ALSO BE
INTERESTED IN:](#)

Flat Type Fusing Press HP-125FA

Standard

Vaccum Emergency Switch

Option

Double Tray (Front and Back · Right and Left)

Consumption

Teflon Sheet
Fabric Cover
Felt Mat

TOP

SPECIFICATIONS

OPTION

YOU MAY ALSO BE
INTERESTED IN:

Flat Type Fusing Press HP-125FA



▶ **HP-125FA (Vaccum Device)**



▶ **HP-124AP**



▶ **HP-124A**