

Flat Type Fusing Press HP-124AP



Specification

- ☐ Motor driven fully-automatic flat type press.
- ☐ Compact and requires no extra equipment such as an air compressor, and can be installed very easily.
- ☐ Uses a special heater and the aluminium heater plates give excellent thermal efficiency and uniform temperature distribution.
- ☐ Anti-static type Teflon sheet is used for the upper plate, making it easy to clean.
- ☐ Although the suction system is automatic, pedal-operation is also possible (when using a tray, pedal-operation can not be used). Electrical contact-pointless components are used to improve the durability of the machine.
- ☐ The powerful 200w blow motor provides extravacuum sucking power, and the sirocco fan is equipped to reduce noise. Sizes and spacings of the suction holes in the center part and around both ends on the lower plate have been properly adjusted, to provide uniform sucking power over the entire surface.

Flat Type Fusing Press HP-124AP



Description	Flat Type Fusing Press
Model	HP-124AP
Voltage	3P22V / 3P380V
Power	Heater : 3,650W Motor : 400W
Max Voltage	3P200V : 13A 1P200V : 22.5A
Temperature (MAX)	200℃
Presser (MAX)	210g/cm2
Plate Size	1,200×400mm
Dimension	Body : 950(D)×1,226(W)×1,340(H)mm Tray : 1,750(D)×1,440(W)×1,340(H)mm
Weight	210kg

■ 対象製品イラスト

イラスト説明



[TOP](#)[SPECIFICATIONS](#)[OPTIONS](#)[YOU MAY ALSO BE
INTERESTED IN:](#)

Flat Type Fusing Press HP-124AP

標準装備

緊急スイッチ バキューム

オプション

ダブルトレイ(前後)

消耗品

テフロンシート
布カバー
フェルトマット

TOP

SPECIFICATIONS

OPTIONS

YOU MAY ALSO BE
INTERESTED IN:

Flat Type Fusing Press HP-124AP



▶ **HP-124AP(Double Tray as Option)**



▶ **HP-125FA**



▶ **HP-124A**