

Rotary Fusing Press HP-800TS



Specification

A strong silicon rubbered roller ensures uniform pressure.

Electric thermostat and S.S.R(Solid State Relay) control the temperature difference to a minimum, and "electrical contactless" components are used.

Belt warping is automatically corrected, therefore, the operator only needs to insert the material.

A smooth-surfaced heat-proof Teflon belt is used, so belt cleaning is easy.

A more powerful and quiet induction motor is used to increase efficiency.

This machine has a larger receiver, which allows stacking of a larger quantity of products.

A touch & open type side cover is used to make inspection and maintenance of the machine easier.

Two cleaners are installed. One is on the belt and the other is on the drum to prevent trouble such as resin strike back.

Castors allow easy movement of the machine therefore its position in the factory can be easily changed.

Rotary Fusing Press HP-800TS



HP-800TS

Description	Rotary Fusing Press
Model	HP-800TS- II
Voltage	3P380V・3P220V
Rated Output	Heater : 4,500W Motor : 90W (Strip-Off Device 25W)
Temperature (MAX)	200℃
Presser (MAX)	500 g /cm ²
Belt Speed (MAX)	6m/分
Heating Time	6～60 Secound
Fusing Width	800mm
Size	1,240(W)×1,115(D)×1,280(H)mm
Weight	230kg

■ 対象製品イラスト



TOP

SPECIFICATIONS

OPTIONS

YOU MAY ALSO BE
INTERESTED IN:

Rotary Fusing Press HP-800TS

Standard

Automatic Belt Warping Device

Consumption

Teflon Belt

TOP

SPECIFICATIONS

OPTIONS

YOU MAY ALSO BE
INTERESTED IN:

Rotary Fusing Press HP-800TS



▶ **HP-800TS – II**



▶ **HP-600LFS**



▶ **HP-900LFS**



▶ **HP-600DA**